



Military-Fasteners.com

P/N AS21919WCJ19

Description

Diameter: 13/64", steel comp 321 band or steel comp 347 band

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS21919WCJ19
Minimum Qty (MOQ):	10
NSN:	5340-01-106-2735
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N AS21919WCJ19 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Heat And Oil Resistant And Weather Resistant
<b>Overall Width:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Diameter:</b>	0.204 Inches Nominal
<b>Material Thickness:</b>	0.0285 Inches Minimum And 0.0355 Inches Maximum
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	1.046 Inches Minimum And 1.076 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	1.264 Inches Minimum And 1.294 Inches Maximum
<b>Loop Inside Diameter:</b>	1.173 Inches Minimum And 1.203 Inches Maximum
<b>Material:</b>	Rubber Cushion
<b>Material:</b>	Steel Comp 321 Band Or Steel Comp 347 Band
<b>Material Document And Classification:</b>	Mil-r-25988 Mil Spec Single Material Response Cushion
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Offset Mount

## How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/AS21919WCJ19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.