

Description

Diameter: 13/64", steel comp 321 band or steel comp 347 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | AS21919WCJ19 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5340-01-106-2735 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N AS21919WCJ19 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Heat And Oil Resistant And Weather Resistant |
| Overall Width: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.0285 Inches Minimum And 0.0355 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 1.046 Inches Minimum And 1.076 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.264 Inches Minimum And 1.294 Inches Maximum |
| Loop Inside Diameter: | 1.173 Inches Minimum And 1.203 Inches Maximum |
| Material: | Rubber Cushion |
| Material: | Steel Comp 321 Band Or Steel Comp 347 Band |
| Material Document And Classification: | Mil-r-25988 Mil Spec Single Material Response Cushion |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/AS21919WCJ19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.