



Military-Fasteners.com

P/N AS21919WDF14

Description

Diameter: 13/64", rubber butadiene-acrylonitrile cushion, AS21919 series clamp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS21919WDF14
Minimum Qty (MOQ):	5
NSN:	5340-00-351-4085
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N AS21919WDF14 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.050 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.893 Inches Minimum And 0.923 Inches Maximum
Distance From Loop Center To Tongue End:	1.126 Inches Nominal
Loop Inside Diameter:	0.860 Inches Minimum And 0.890 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material Document And Classification:	Ams 3215 Assn Std Single Material Response Cushion
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/AS21919WDF14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.