

Description

Diameter: 13/64", rubber butadiene-acrylonitrile class nbr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | AS21919WDF32 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5340-01-528-0571 |
| Schedule B: | 7616.10.1000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N AS21919WDF32 Specifications

| | |
|--|---|
| Tongue Hole Type: | Round, Unthreaded |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.208 Inches Minimum And 0.218 Inches Maximum |
| Material Thickness: | 0.040 Inches Nominal |
| End Item Identification: | Nh-2/h-60 |
| Material Diameter: | 0.125 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.475 Inches Nominal |
| Distance From Loop Center To Tongue End: | 1.694 Inches Nominal |
| Loop Inside Diameter: | 2.000 Inches Nominal |
| Material: | Aluminum Alloy 2024 Band |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr Cushion |
| Material Document And Classification: | Mil-c-85052/1 Mil Spec Single Material Response Cushion |
| Material Document And Classification: | Qq-a-250/5 Fed Spec Single Material Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/AS21919WDF32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.