

P/N AS21919WDF32

Description

Diameter: 13/64", rubber butadiene-acrylonitrile class nbr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS21919WDF32
Minimum Qty (MOQ):	5
NSN:	5340-01-528-0571
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N AS21919WDF32 Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.208 Inches Minimum And 0.218 Inches Maximum
Material Thickness:	0.040 Inches Nominal
End Item Identification:	Nh-2/h-60
Material Diameter:	0.125 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.475 Inches Nominal
Distance From Loop Center To Tongue End:	1.694 Inches Nominal
Loop Inside Diameter:	2.000 Inches Nominal
Material:	Aluminum Alloy 2024 Band
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material Document And Classification:	Mil-c-85052/1 Mil Spec Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/AS21919WDF32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WDF32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WDF32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WDF32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/asa1919WDF32 and selecting the property of the property of