



Military-Fasteners.com

P/N AS21919WDF48

Description

Diameter: 13/64", rubber butadiene-acrylonitrile class nbr cushion

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS21919WDF48
Minimum Qty (MOQ):	5 EA
NSN:	5340-00-579-8061
Schedule B:	7616.99.5090
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N AS21919WDF48 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.204 Inches Nominal
Material Thickness:	0.063 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	1.985 Inches Minimum And 2.015 Inches Maximum
Distance From Loop Center To Tongue End:	2.218 Inches Nominal
Loop Inside Diameter:	2.985 Inches Minimum And 3.015 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr Cushion
Material Document And Classification:	Ams 3215 Assn Std Single Material Response Cushion
Material Document And Classification:	Qq-a-250/5 Fed Spec Single Material Response Band
Surface Treatment:	Chromate Band
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Band
Style Designator:	Offset Mount
Nondefinitive Spec/std Data:	2 Type And B Class

How to Order

Order this cushioned loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/AS21919WDF48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.