

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AS2230308
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-992-5585
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AS2230-308 Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.181 Inches Minimum And 0.193 Inches Maximum
Countersink Angle:	120.0 Degrees Nominal
Special Features:	Colored Violet For Identification
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AS2230-308> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.