

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | AS2230308 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-00-992-5585 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N AS2230-308 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.091 Inches Minimum And 0.096 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.181 Inches Minimum And 0.193 Inches Maximum |
| Countersink Angle: | 120.0 Degrees Nominal |
| Special Features: | Colored Violet For Identification |
| Material: | Aluminum Alloy Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AS2230-308> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.