

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AS2230308
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-992-5585
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N AS2230-308 Specifications

<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.091 Inches Minimum And 0.096 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.181 Inches Minimum And 0.193 Inches Maximum
<b>Countersink Angle:</b>	120.0 Degrees Nominal
<b>Special Features:</b>	Colored Violet For Identification
<b>Material:</b>	Aluminum Alloy Overall
<b>Surface Treatment:</b>	Anodize Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AS2230-308> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.