



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N AS2230-408**

## Description

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AS2230408
Minimum Qty (MOQ):	200
NSN:	5320-00-012-2324
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N AS2230-408 Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.121 Inches Minimum And 0.127 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.244 Inches Minimum And 0.256 Inches Maximum
Countersink Angle:	120.0 Degrees Nominal
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AS2230-408> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.