

## P/N AS3085-011

### **Description**

high temp, fluid resistant, low compression set, fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: AS3085011

Minimum Qty (MOQ): 25

NSN: 5331-00-166-0975

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N AS3085-011 Specifications

Outside Diameter:	0.430 Inches Minimum And 0.452 Inches Maximum
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.296 Inches Minimum And 0.306 Inches Maximum
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm
Material Document And Classification:	Ams7276 Assn Std Single Material Response

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/AS3085-011">https://military-fasteners.com/o\_rings/o\_rings/AS3085-011</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/AS3085-011">https://military-fasteners.com/o\_rings/o\_rings/AS3085-011</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/AS3085-011">https://military-fasteners.com/o\_rings/o\_rings/AS3085-011</a> and selecting the quantity you want then click "add to cart".