

# P/N AS3085-015

Military-Fasteners.com

#### Description

high temp, fluid resistant - low compression set, fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	AS3085015
Minimum Qty (MOQ):	100
NSN:	5331-00-166-0991
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



## P/N AS3085-015 Specifications

Outside Diameter:	0.691 Inches Nominal
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.544 Inches Minimum And 0.558 Inches Maximum
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Part Name Assigned By Controlling Agency:	Packing, Preformed-"o"ring, Mil-r-83248, 75 Durometer
Special Features:	Low Compression Set
Color:	Black
Material:	Rubber Fluorocarbon Class Fpm
Material Document And Classification:	Mil-r-83248 Type I, Class 1 Mil Spec Single Material Response

### How to Order

Order this o-ring from our inventory online by visiting <u>https://military-fasteners.com/o\_rings/o\_rings/AS3085-015</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.