

Description

high temp, fluid resistant - low compression set, fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS3085019
Minimum Qty (MOQ):	100
NSN:	5331-01-279-3359
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N AS3085-019 Specifications

<b>Temp Rating:</b>	-5.0 Deg Celsius And 205.0 Deg Celsius
<b>Cross-sectional Height:</b>	0.067 Inches Minimum And 0.073 Inches Maximum
<b>Center Hole Diameter:</b>	0.792 Inches Minimum And 0.810 Inches Maximum
<b>End Item Identification:</b>	2840-99-645-9394;2840-99-645-9395;2840-99-766-0507;2840-99-766-0508;model Rb199mk101/103/104;similar To Nsn 5330-01-044-0785
<b>Hardness Rating:</b>	70.0 Shore Durometer A Minimum And 80.0 Shore Durometer A Maximum
<b>Special Features:</b>	O-ring Shape;operated By Fluid, High Temperature
<b>Color:</b>	Brown
<b>Material:</b>	Rubber Polymethylene-perfluoroalkylene Class Fkm
<b>Material Document And Classification:</b>	Ams7280 Assn Std Single Material Response Or Astm D2000/sae J200 Assn Std Single Material Response
<b>Reference Number Differentiating Characteristics:</b>	As Diff By Spec K2617 Hte7300 Performance Rqmt Tornado Acft Engine Model Rb199

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/AS3085-019](https://military-fasteners.com/o_rings/o_rings/AS3085-019) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.