

## Description

high temp, fluid resistant - low compression set, fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AS3085024
Minimum Qty (MOQ):	15
NSN:	5331-00-166-1020
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N AS3085-024 Specifications

<b>Outside Diameter:</b>	1.238 Inches Minimum And 1.270 Inches Maximum
<b>Outside Diameter:</b>	1.171 Inches Minimum And 1.197 Inches Maximum
<b>Temp Rating:</b>	-15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.067 Inches Minimum And 0.073 Inches Maximum
<b>Center Hole Diameter:</b>	1.104 Inches Minimum And 1.124 Inches Maximum
<b>Hardness Rating:</b>	75.0 Shore Durometer A Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Packing,preformed-"o"ring, Mil-r-83248, 75 Durometer
<b>Special Features:</b>	Flight Safety Critical Aircraft Part
<b>Color:</b>	Black
<b>Material:</b>	Rubber Fluorocarbon Class Fpm
<b>Material Document And Classification:</b>	Mil-r-83248 Type I, Class 1 Mil Spec Single Material Response

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/AS3085-024](https://military-fasteners.com/o_rings/o_rings/AS3085-024) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.