

**Description**

high temp, fluid resistant, low compression set rubber ring, AS3085 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AS3085123
Minimum Qty (MOQ):	50
NSN:	5331-01-277-6600
Schedule B:	4016.99.6050
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N AS3085-123 Specifications

<b>Temp Rating:</b>	-5.0 Deg Celsius And 205.0 Deg Celsius
<b>Cross-sectional Height:</b>	0.100 Inches Minimum And 0.106 Inches Maximum
<b>Center Hole Diameter:</b>	1.162 Inches Minimum And 1.186 Inches Maximum
<b>End Item Identification:</b>	2840-99-645-9394; 2840-99-645-9395; 2840-99-766-0507; 2840-99-766-0508
<b>Color:</b>	Brown
<b>Material:</b>	Rubber Polymethylene-perfluoroalkylene Class Fkm
<b>Reference Number Differentiating Characteristics:</b>	As Diff By Spec K2617 Hte7300 Performance Rqmt Tornado Acft Engine Model Rb199

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/AS3085-123](https://military-fasteners.com/o_rings/o_rings/AS3085-123) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.