

Description

High temp, fluid resistant, very low compression set, fluorocarbon rubber ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

M83248/1-904

SKU / Model:	AS320804
Minimum Qty (MOQ):	25
NSN:	5331-00-103-1986
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N AS3208-04 Specifications

Outside Diameter:	0.495 Inches Nominal
Temp Rating:	-20.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Cross-sectional Height:	0.069 Inches Minimum And 0.075 Inches Maximum
Center Hole Diameter:	0.346 Inches Minimum And 0.356 Inches Maximum
lil End Item Identification:	Mrap - Cougar Cat1 A1; Mrap - Cougar Cat1 A2; Mrap - Cougar Cat2 A1; Mrap - Cougar Cat2 A2
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/AS3208-04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.