

Description

High temp, fluid resistant, very low compression set, fluorocarbon rubber ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

M83248/1-905

SKU / Model:	AS320805
Minimum Qty (MOQ):	20
NSN:	5331-00-167-5166
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N AS3208-05 Specifications

Outside Diameter:	0.547 Inches Minimum And 0.569 Inches Maximum
Cross-sectional Height:	0.069 Inches Minimum And 0.075 Inches Maximum
Center Hole Diameter:	0.409 Inches Minimum And 0.419 Inches Maximum
End Item Identification:	Stream (std. Tensioned Replenishment At Sea Method); Elevators, Aircraft; Aircraft, Airlifter C-17a; Boilers, 1200 Psi; Aircraft, Sof (Ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; L.p. Compressors; Stern Gates; Systems, 02n2; Sas (starting Air Sys), Ffg-7; 2320-01-097-0260 Hemtt (heavy Expanded Mobility Tactical Trucks) Bap (bridge Adapter Pallet).
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/AS3208-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.