

Description

high temp, fluid resistant, very low compression set, fluorocarbon rubber, AS3208 series oring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS320810
Minimum Qty (MOQ):	25
NSN:	5331-00-020-0067
Schedule B:	4016.93.5010
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N AS3208-10 Specifications

Outside Diameter:	0.934 Inches Minimum And 0.964 Inches Maximum
Temp Rating:	-15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Cross-sectional Height:	0.094 Inches Minimum And 0.100 Inches Maximum
Center Hole Diameter:	0.746 Inches Minimum And 0.764 Inches Maximum
End Item Identification:	Mrap - Cougar Cat1; Mrap - M-atv Ui
Elongation Percentage:	125 Maximum
Hardness Rating:	70.0 Shore Durometer A Minimum And 80.0 Shore Durometer A Maximum
Material:	Rubber Fluorocarbon Class Fpm
Material Document And Classification:	Mil-r-83248, CI1 Mil Spec Single Material Response
Nondefinitive Spec/std Data:	1 Type And 1 Class

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/AS3208-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.