



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N AS3209-013**

## Description

high temp, fluid resistant, very low compression set, fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AS3209013
Minimum Qty (MOQ):	50
NSN:	5331-00-166-0988
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N AS3209-013 Specifications

<b>Outside Diameter:</b>	0.555 Inches Minimum And 0.577 Inches Maximum
<b>Cross-sectional Height:</b>	0.067 Inches Minimum And 0.073 Inches Maximum
<b>Center Hole Diameter:</b>	0.421 Inches Minimum And 0.431 Inches Maximum
<b>Elongation Percentage:</b>	125 Maximum
<b>Hardness Rating:</b>	75.0 Shore Durometer A Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Packing,preformed
<b>Material:</b>	Rubber Fluorocarbon Class Fpm
<b>Material Document And Classification:</b>	Ams 7276 Assn Std Single Material Response

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/AS3209-013](https://military-fasteners.com/o_rings/o_rings/AS3209-013) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.