

## P/N AS3209-018

## **Description**

high temp, fluid resistant, very low compression set, fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

M83248-1-018 M83248/1-018

SKU / Model: AS3209018

Minimum Qty (MOQ): 20

NSN: 5331-00-166-0994

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N AS3209-018 Specifications

| Outside Diameter:       | 0.864 Inches Minimum And 0.894 Inches Maximum |
|-------------------------|---|
| Cross-sectional Height: | 0.067 Inches Minimum And 0.073 Inches Maximum |
| Center Hole Diameter:   | 0.730 Inches Minimum And 0.748 Inches Maximum |
| Elongation Percentage:  | 125 Maximum                                   |
| Hardness Rating:        | 75.0 Shore Durometer A Nominal                |
| Material:               | Rubber Fluorocarbon Class Fpm                 |

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/o\_rings/AS3209-018">https://military-fasteners.com/o\_rings/o\_rings/AS3209-018</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/o\_rings/AS3209-018">https://military-fasteners.com/o\_rings/o\_rings/AS3209-018</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/AS3209-018">https://military-fasteners.com/o\_rings/o\_rings/AS3209-018</a> and selecting the quantity you want then click "add to cart".