



★ FASTENERS

Military-Fasteners.com

P/N AS3209-022

## Description

High temp, fluid resistant, very low compression set, fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AS3209022
Minimum Qty (MOQ):	50
NSN:	5331-00-166-1011
Schedule B:	4016.93.5010
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N AS3209-022 Specifications

<b>Outside Diameter:</b>	1.113 Inches Minimum And 1.145 Inches Maximum
<b>Temp Rating:</b>	-15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.067 Inches Minimum And 0.073 Inches Maximum
<b>Center Hole Diameter:</b>	0.979 Inches Minimum And 0.999 Inches Maximum
<b>Elongation Percentage:</b>	125 Maximum
<b>Hardness Rating:</b>	75.0 Shore Durometer A Nominal
<b>Material:</b>	Rubber Fluorocarbon Class Fpm

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/AS3209-022](https://military-fasteners.com/o_rings/o_rings/AS3209-022) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.