

## P/N AS3209-023

### **Description**

AS3209-023 O-Ring

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AS3209023

Minimum Qty (MOQ): 50

NSN: 5331-00-166-1017

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N AS3209-023 Specifications

Outside Diameter:	1.175 Inches Minimum And 1.207 Inches Maximum
Outside Diameter:	1.175 Inches Nominal
Temp Rating:	-30.0 Deg Fahrenheit And 500.0 Deg Fahrenheit
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	1.041 Inches Minimum And 1.061 Inches Maximum
Elongation Percentage:	125 Maximum
Elongation Percentage:	125 Nominal
Hardness Rating:	70.0 Shore Durometer A Minimum And 80.0 Shore Durometer A Maximum
Material:	Rubber Fluorocarbon Class Fpm
Material Document And Classification:	Mil-r-83248,cl 1 Mil Spec Single Material Response
Nondefinitive Spec/std Data:	1 Type And 1 Class

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o rings/AS3209-023">https://military-fasteners.com/o rings/AS3209-023</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o rings/AS3209-023">https://military-fasteners.com/o rings/AS3209-023</a> and selecting the quantity you want then click "add to cart".