

Description

high temp fluid resistant very low compression set flurocarbon rubber ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[M83248/1-038](#)

SKU / Model:	AS3209038
Minimum Qty (MOQ):	20
NSN:	5331-00-166-8397
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N AS3209-038 Specifications

Outside Diameter:	2.728 Inches Minimum And 2.780 Inches Maximum
Temp Rating:	-15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	2.594 Inches Minimum And 2.634 Inches Maximum
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/AS3209-038 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.