

Description

high temp fluid resistant, very low compression set fluorocarbon rubber ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS3209120
Minimum Qty (MOQ):	25
NSN:	5331-00-103-1579
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N AS3209-120 Specifications

<b>Outside Diameter:</b>	1.193 Inches Nominal
<b>Temp Rating:</b>	-20.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.100 Inches Minimum And 0.106 Inches Maximum
<b>Center Hole Diameter:</b>	0.977 Inches Minimum And 0.997 Inches Maximum
<b>Elongation Percentage:</b>	125 Maximum
<b>Hardness Rating:</b>	75.0 Shore Durometer A Nominal
<b>Material:</b>	Rubber Fluorocarbon Class Fpm

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/AS3209-120](https://military-fasteners.com/o_rings/o_rings/AS3209-120) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.