

P/N AS3209-120

Description

high temp fluid resistant, very low compression set flurocarbon rubber ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AS3209120

Minimum Qty (MOQ): 25

NSN: 5331-00-103-1579

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi







^{*} See page 2 for technical characteristics

P/N AS3209-120 Specifications

Outside Diameter:	1.193 Inches Nominal
Temp Rating:	-20.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	0.977 Inches Minimum And 0.997 Inches Maximum
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/AS3209-120 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/AS3209-120 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/AS3209-120 and selecting the quantity you want then click "add to cart".