

P/N AS3209-123

Military-Fasteners.com

## Description

high temp fluid resistant very low compression set flurocarbon rubber ring

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

<u>M83248/1-123</u>	
SKU / Model:	AS3209123
Minimum Qty (MOQ):	25
NSN:	5331-00-167-5112
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



# P/N AS3209-123 Specifications

Outside Diameter:	1.362 Inches Minimum And 1.398 Inches Maximum
Temp Rating:	-15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	1.162 Inches Minimum And 1.186 Inches Maximum
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm

# How to Order

Order this o-ring from our inventory online by visiting <u>https://military-fasteners.com/o\_rings/o\_rings/AS3209-123</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.