

P/N AS3209-141

Military-Fasteners.com

#### Description

high temp, fluid resistant, very low compression set flurocarbon rubber ring

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model:	AS3209141
Minimum Qty (MOQ):	25
NSN:	5331-00-330-3307
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi
	FASTENERS   Image: Complete grad (complete projection)   Image: Complete grad (complete grad (complete projection)   Image: Complete grad (complete grad (com

# P/N AS3209-141 Specifications

Outside Diameter:	2.480 Inches Minimum And 2.532 Inches Maximum
Temp Rating:	-15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	2.280 Inches Minimum And 2.320 Inches Maximum
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm

## How to Order

Order this o-ring from our inventory online by visiting <u>https://military-fasteners.com/o\_rings/o\_rings/AS3209-141</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.