

Description

high temp, fluid resistant - very low compression set, fluorocarbon rubber ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AS3209213 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5331-00-165-1940 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |

NO IMAGE
AVAILABLE

P/N AS3209-213 Specifications

| | |
|--------------------------------|---|
| Outside Diameter: | 1.181 Inches Minimum And 1.217 Inches Maximum |
| Temp Rating: | -15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit |
| Cross-sectional Height: | 0.135 Inches Minimum And 0.143 Inches Maximum |
| Center Hole Diameter: | 0.911 Inches Minimum And 0.931 Inches Maximum |
| Elongation Percentage: | 125 Maximum |
| Hardness Rating: | 75.0 Shore Durometer A Nominal |
| Material: | Rubber Fluorocarbon Class Fpm |

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/AS3209-213 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.