

P/N AS3209-216

Military-Fasteners.com

Description

high temp fluid resistant very low compression set flurocarbon rubber ring

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AS3209216
Minimum Qty (MOQ):	10
NSN:	5331-00-165-1942
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N AS3209-216 Specifications

Outside Diameter:	1.367 Inches Minimum And 1.407 Inches Maximum
Temp Rating:	-15.0 Deg Fahrenheit And 400.0 Deg Fahrenheit
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	1.097 Inches Minimum And 1.121 Inches Maximum
Elongation Percentage:	125 Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Fluorocarbon Class Fpm

How to Order

Order this o-ring from our inventory online by visiting <u>https://military-fasteners.com/o_rings/o_rings/AS3209-216</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.