

Description

AS3220-04 Tube Fitting Flared Sleeve

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS322004
Minimum Qty (MOQ):	10
NSN:	4730-01-567-3229
ECCN:	EAR99



* See page 2 for technical characteristics

P/N AS3220-04 Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.390 Inches Minimum And 0.422 Inches Maximum
Flange Width:	0.125 Inches Minimum And 0.157 Inches Maximum
Flange Outside Diameter:	0.383 Inches Minimum And 0.386 Inches Maximum
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	0.294 Inches Minimum And 0.297 Inches Maximum
Hose/tube Outside Diameter For Which Designed:	0.250 Inches Nominal
Material:	Aluminum Alloy, Qq-a-225/4 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024
Material:	Aluminum Alloy 2014 Or Aluminum Alloy 2024
Surface Treatment:	Anodize
Style Designator:	Sleeve
Surface Treatment:	Anodized

How to Order

Order this tube fitting flared sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/AS3220-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.