

Description

AS3220-04 Tube Fitting Flared Sleeve

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | AS322004 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 4730-01-567-3229 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N AS3220-04 Specifications

| | |
|---|--|
| Casehardening Indicator: | Not Casehardened |
| Overall Length: | 0.390 Inches Minimum And 0.422 Inches Maximum |
| Flange Width: | 0.125 Inches Minimum And 0.157 Inches Maximum |
| Flange Outside Diameter: | 0.383 Inches Minimum And 0.386 Inches Maximum |
| Seat Angle In Deg: | 33.0 |
| Sleeve Outside Diameter: | 0.294 Inches Minimum And 0.297 Inches Maximum |
| Hose/tube Outside Diameter For Which Designed: | 0.250 Inches Nominal |
| Material: | Aluminum Alloy, Qq-a-225/4 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024 |
| Material: | Aluminum Alloy 2014 Or Aluminum Alloy 2024 |
| Surface Treatment: | Anodize |
| Style Designator: | Sleeve |
| Surface Treatment: | Anodized |

How to Order

Order this tube fitting flared sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/AS3220-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.