

Description

AS3236-08 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS323608
Minimum Qty (MOQ):	10
NSN:	5306-01-567-6926
ECCN:	EAR99



* See page 2 for technical characteristics

P/N AS3236-08 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.543 Inches Maximum
Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.248 Inches Minimum And 0.268 Inches Maximum
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum
First Diameter From Head:	0.165 Inches Minimum And 0.175 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.092 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Externally Relieved Body Diameter Quantity:	1
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/AS3236-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.