

## **P/N AS3578-008**

### **Description**

supersedes ms9021 fuel and low temperature resistant aerospace nitrile

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AS3578008

Minimum Qty (MOQ): 25

NSN: 5331-00-618-3447

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N AS3578-008 Specifications

Outside Diameter:	0.305 Inches Minimum And 0.327 Inches Maximum
Temp Rating:	-70.0 Deg Fahrenheit And 180.0 Deg Fahrenheit
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.171 Inches Minimum And 0.181 Inches Maximum
Hardness Rating:	65.0 Shore Durometer A Nominal
Material:	Rubber Butadiene-acrylonitrile Class Nbr
Material Document And Classification:	Ams7271 Assn Std Single Material Response

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/o\_rings/AS3578-008">https://military-fasteners.com/o\_rings/o\_rings/AS3578-008</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/o\_rings/AS3578-008">https://military-fasteners.com/o\_rings/o\_rings/AS3578-008</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/AS3578-008">https://military-fasteners.com/o\_rings/o\_rings/AS3578-008</a> and selecting the quantity you want then click "add to cart".