

## P/N AS3580-3-10

## **Description**

Fastener Length: 5/8", Thread: 10-32, Thread Length: 17/32", drilled head, AS3580 series bolt

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

SKU / Model: AS3580310

Minimum Qty (MOQ):

NSN: 5306-01-535-0297

ECCN: EAR99







# P/N AS3580-3-10 Specifications

Thread Class:	32
Thread Direction:	Right-hand
Thread Length:	0.533 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.258 Inches Nominal
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.120 Inches Minimum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	185000 Pounds Per Square Inch
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/AS3580-3-10">https://military-fasteners.com/bolts/machine+bolts/AS3580-3-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.