

P/N AS3580-3-10

Military-Fasteners.com

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 17/32", drilled head, AS3580 series bolt

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | AS3580310 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-01-535-0297 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N AS3580-3-10 Specifications

| Thread Class: | 32 |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.533 Inches Maximum |
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.258 Inches Nominal |
| Width Between Flats: | 0.250 Inches Nominal |
| Extended Washer Diameter: | 0.375 Inches Nominal |
| Extended Washer Thickness: | 0.120 Inches Minimum |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 185000 Pounds Per Square Inch |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5662 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AS3580-3-10</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.