

**Description**

Fastener Length: 5/8", Thread: 10-32, Thread Length: 17/32", drilled head, AS3580 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AS3580310
Minimum Qty (MOQ):	10
NSN:	5306-01-535-0297
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N AS3580-3-10 Specifications

<b>Thread Class:</b>	32
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.533 Inches Maximum
<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Double Hexagon Extended Washer
<b>Head Height:</b>	0.258 Inches Nominal
<b>Width Between Flats:</b>	0.250 Inches Nominal
<b>Extended Washer Diameter:</b>	0.375 Inches Nominal
<b>Extended Washer Thickness:</b>	0.120 Inches Minimum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	185000 Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams 5662 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AS3580-3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.