



Military-Fasteners.com

P/N AS5168D16

Description

Thread: 1.312 Inches, 37.0 degree, flared, AS5168 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24404D16](#) [AN806D16](#) [AS5168W16](#)

SKU / Model:	AS5168D16
Minimum Qty (MOQ):	2
NSN:	4730-00-287-0118
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N AS5168D16 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.328 Inches Minimum And 0.370 Inches Maximum
Overall Length:	0.370 Inches Minimum And 0.391 Inches Maximum
End Item Identification:	Grumman A-10 Aircraft
iii End Item Identification:	Grumman A-10 Aircraft; Mrap Buffalo Mk2a2
Connection Style:	Flared
Thread Quantity Per Inch:	12 External
Nominal Thread Size:	1.312 Inches External
Seat Angle:	37.0 Degrees
Special Features:	Drilled Hole,0.828 In.id By 0.391 In.deep At Bottom
Material:	Aluminum Alloy 2014 Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec 1st Material Response Or Qq-a-225/6,t6 Fed Spec 2nd Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Cl 2 Mil Spec Single Treatment Response Overall
Style Designator:	C42 Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic)
Style Designator:	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Un External

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/AS5168D16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.