

Description

tube outer diameter: 1-1/4", thread: 1-5/8-12, 37i□ , flared tube plug aluminum"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS5168D20
Minimum Qty (MOQ):	1
NSN:	4730-00-640-5104
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE
AVAILABLE

P/N AS5168D20 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.401 Inches Nominal
Overall Length:	1.359 Inches Nominal
End Item Identification:	Aircraft Fluid System
Connection Style:	Flared
Thread Quantity Per Inch:	12 External
Maximum Operating Pressure:	1500.0 Pounds Per Square Inch
Nominal Thread Size:	1.625 Inches External
Seat Angle:	37.0 Degrees
Special Features:	Grumman Aircraft Corp,a-10 Aircraft Model
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec Single Material Response Overall Or 11-a-225/6,t6 Or T851 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Style Designator:	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Un External
Specification/standard Data:	96906-ms24404 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AS5168D20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.