

**Description**

tube outer diameter: 1-1/4", thread: 1-5/8-12, 37i□ , flared tube plug aluminum"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AS5168D20
Minimum Qty (MOQ):	1
NSN:	4730-00-640-5104
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE  
AVAILABLE

## P/N AS5168D20 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Head Height:</b>	0.401 Inches Nominal
<b>Overall Length:</b>	1.359 Inches Nominal
<b>End Item Identification:</b>	Aircraft Fluid System
<b>Connection Style:</b>	Flared
<b>Thread Quantity Per Inch:</b>	12 External
<b>Maximum Operating Pressure:</b>	1500.0 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	1.625 Inches External
<b>Seat Angle:</b>	37.0 Degrees
<b>Special Features:</b>	Grumman Aircraft Corp,a-10 Aircraft Model
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Qq-a-225/4,t6 Fed Spec Single Material Response Overall Or 11-a-225/6,t6 Or T851 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2,class 2 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
<b>Style Designator:</b>	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic)
<b>Thread Series Designator:</b>	Un External
<b>Specification/standard Data:</b>	96906-ms24404 Government Standard

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AS5168D20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.