

Description

tube outer diameter: 3/16", thread: 3/8-24, flared tube plug corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN806J3](#)

SKU / Model:	AS5168J03
Minimum Qty (MOQ):	2
NSN:	4730-00-825-5401
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N AS5168J03 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.178 Inches Minimum And 0.208 Inches Maximum
Overall Length:	0.672 Inches Nominal
Maximum Operating Temp:	250.0 Deg Fahrenheit
Connection Style:	Flared
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.375 Inches External
Seat Angle:	37.0 Degrees
Material:	Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Media For Which Designed:	Air
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Thread Series Designator:	Unf External
Specification/standard Data:	81349-mil-f-5509 Government Specification

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AS5168J03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.