

**Description**

tube outer diameter: 3/16", thread: 3/8-24, flared tube plug corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AN806J3](#)

SKU / Model:	AS5168J03
Minimum Qty (MOQ):	2
NSN:	4730-00-825-5401
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



\* See page 2 for technical characteristics

## P/N AS5168J03 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Head Height:</b>	0.178 Inches Minimum And 0.208 Inches Maximum
<b>Overall Length:</b>	0.672 Inches Nominal
<b>Maximum Operating Temp:</b>	250.0 Deg Fahrenheit
<b>Connection Style:</b>	Flared
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.375 Inches External
<b>Seat Angle:</b>	37.0 Degrees
<b>Material:</b>	Steel Comp 304 Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Media For Which Designed:</b>	Air
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
<b>Thread Series Designator:</b>	Unf External
<b>Specification/standard Data:</b>	81349-mil-f-5509 Government Specification

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AS5168J03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.