

**Description**

tube outer diameter: 3/8", thread: 9/16-18, 37°<sup>∞</sup>, flared tube plug corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AN806J6](#)

SKU / Model:	AS5168J06
Minimum Qty (MOQ):	5
NSN:	4730-01-548-1236
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AS5168J06 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Head Height:</b>	0.250 Inches Nominal
<b>Overall Length:</b>	0.812 Inches Nominal
<b>Maximum Operating Temp:</b>	475.0 Deg Fahrenheit
<b>End Item Identification:</b>	Misc Bulk Items
<b>Connection Style:</b>	Flared
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.562 Inches External
<b>Seat Angle:</b>	37.0 Degrees
<b>Part Name Assigned By Controlling Agency:</b>	Fitting, Plug, Tube End Flared
<b>Special Features:</b>	304 Stainless Steel; Also Used As Cap, Protective Dust
<b>Material:</b>	Steel Comp 304 Overall
<b>Material Document And Classification:</b>	Qq-s-763 Fed Spec Single Material Response Overall Or Ams 5639 National Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35, Type Vi Or Vii Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
<b>Thread Series Designator:</b>	Unjf External

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AS5168J06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.