

Description

tube outer diameter: 3/8", thread: 9/16-18, 37° flared tube plug corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN806J6](#)

| | |
|-------------------------|--|
| SKU / Model: | AS5168J06 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 4730-01-548-1236 |
| ECCN: | EAR99 |
| National Motor Freight: | 051420, Conduits,o / T Earthen:pipe Fittings |

NO IMAGE
AVAILABLE

P/N AS5168J06 Specifications

| | |
|---|---|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Head Height: | 0.250 Inches Nominal |
| Overall Length: | 0.812 Inches Nominal |
| Maximum Operating Temp: | 475.0 Deg Fahrenheit |
| End Item Identification: | Misc Bulk Items |
| Connection Style: | Flared |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch |
| Nominal Thread Size: | 0.562 Inches External |
| Seat Angle: | 37.0 Degrees |
| Part Name Assigned By Controlling Agency: | Fitting, Plug, Tube End Flared |
| Special Features: | 304 Stainless Steel; Also Used As Cap, Protective Dust |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | Qq-s-763 Fed Spec Single Material Response Overall Or Ams 5639 National Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35, Type Vi Or Vii Fed Spec Single Treatment Response Overall |
| Style Designator: | Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic |
| Thread Series Designator: | Unjf External |

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AS5168J06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.