

Description

tube outer diameter: 3/8", thread: 9/16-18, 37°, flared tube plug corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AN806J6](#)

SKU / Model:	AS5168J06
Minimum Qty (MOQ):	5
NSN:	4730-01-548-1236
ECCN:	EAR99
National Motor Freight:	051420, Conduits,o / T Earthen:pipe Fittings



* See page 2 for technical characteristics

P/N AS5168J06 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.250 Inches Nominal
Overall Length:	0.812 Inches Nominal
Maximum Operating Temp:	475.0 Deg Fahrenheit
End Item Identification:	Misc Bulk Items
Connection Style:	Flared
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.562 Inches External
Seat Angle:	37.0 Degrees
Part Name Assigned By Controlling Agency:	Fitting, Plug, Tube End Flared
Special Features:	304 Stainless Steel; Also Used As Cap, Protective Dust
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall Or Ams 5639 National Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35, Type Vi Or Vii Fed Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Thread Series Designator:	Unjf External

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AS5168J06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.