

P/N AS5169-06

Description

tube outer diameter: 3/8", thread: 9/16-18, steel"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AS516906
Minimum Qty (MOQ):	1
NSN:	5365-00-287-0103
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9



^{*} See page 2 for technical characteristics

P/N AS5169-06 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.388 Inches Nominal External
Head Height:	0.297 Inches Nominal
Overall Length:	0.719 Inches Nominal
Connection Style:	Plain
Body Core Diameter:	0.296 Inches Nominal
Core Depth:	0.343 Inches Minimum And 0.359 Inches Maximum
Bleeder Hole Center To Threaded End Distance:	0.188 Inches Minimum And 0.250 Inches Maximum
Bleeder Hole Diameter:	0.062 Inches Nominal
Nominal Thread Size:	0.562 Inches External
Seat Angle:	45.0 Degrees
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Unf External

How to Order

Order this machine thread plug from our inventory online by visiting https://military-fasteners.com/fittings/machine+thread+plugs/AS5169-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.