

Description

tube outer diameter: 3/8", thread: 9/16-18, steel"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | AS516906 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5365-00-287-0103 |
| Schedule B: | 7318.29.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

P/N AS5169-06 Specifications

| | |
|--|---|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Thread Length: | 0.388 Inches Nominal External |
| Head Height: | 0.297 Inches Nominal |
| Overall Length: | 0.719 Inches Nominal |
| Connection Style: | Plain |
| Body Core Diameter: | 0.296 Inches Nominal |
| Core Depth: | 0.343 Inches Minimum And 0.359 Inches Maximum |
| Bleeder Hole Center To Threaded End Distance: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Bleeder Hole Diameter: | 0.062 Inches Nominal |
| Nominal Thread Size: | 0.562 Inches External |
| Seat Angle: | 45.0 Degrees |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Style Designator: | Plug, Machine W/bleeder Holes |
| Thread Series Designator: | Unf External |

How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.