

Description

tube outer diameter: 1/2", thread: 3/4-16, steel - with lockwire holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[AN814-8](#)

SKU / Model:

AS516908

Minimum Qty (MOQ):

1

NSN:

5365-00-287-0105

Schedule B:

7307.19.9090

ECCN:

EAR99

National Motor Freight:

095190, Hardware, Noi Sub 9



P/N AS5169-08 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.375 Inches Nominal External
Head Height:	0.312 Inches Nominal
Overall Length:	0.781 Inches Nominal
Connection Style:	Plain
Body Core Diameter:	0.390 Inches Nominal
Core Depth:	0.343 Inches Minimum And 0.359 Inches Maximum
Bleeder Hole Center To Threaded End Distance:	0.219 Inches Minimum And 0.281 Inches Maximum
Bleeder Hole Diameter:	0.062 Inches Nominal
Nominal Thread Size:	0.750 Inches External
Seat Angle:	45.0 Degrees
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Unf External

How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.