

Description

tube outer diameter: 1/2", thread: 3/4-16, steel - with lockwire holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[AN814-8](#)

SKU / Model:

AS516908

Minimum Qty (MOQ):

1

NSN:

5365-00-287-0105

Schedule B:


7307.19.9090

ECCN:

EAR99

National Motor Freight:

095190, Hardware, Noi Sub 9



P/N AS5169-08 Specifications

| | |
|------------------------------------------------------|-----------------------------------------------|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Thread Length: | 0.375 Inches Nominal External |
| Head Height: | 0.312 Inches Nominal |
| Overall Length: | 0.781 Inches Nominal |
| Connection Style: | Plain |
| Body Core Diameter: | 0.390 Inches Nominal |
| Core Depth: | 0.343 Inches Minimum And 0.359 Inches Maximum |
| Bleeder Hole Center To Threaded End Distance: | 0.219 Inches Minimum And 0.281 Inches Maximum |
| Bleeder Hole Diameter: | 0.062 Inches Nominal |
| Nominal Thread Size: | 0.750 Inches External |
| Seat Angle: | 45.0 Degrees |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Style Designator: | Plug, Machine W/bleeder Holes |
| Thread Series Designator: | Unf External |

How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.