

**Description**

tube outer diameter: 1/2", thread: 3/4-16, steel - with lockwire holes

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[AN814-8](#)

SKU / Model:	AS516908
Minimum Qty (MOQ):	1
NSN:	5365-00-287-0105
Schedule B:	7307.19.9090
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



## P/N AS5169-08 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Thread Length:</b>	0.375 Inches Nominal External
<b>Head Height:</b>	0.312 Inches Nominal
<b>Overall Length:</b>	0.781 Inches Nominal
<b>Connection Style:</b>	Plain
<b>Body Core Diameter:</b>	0.390 Inches Nominal
<b>Core Depth:</b>	0.343 Inches Minimum And 0.359 Inches Maximum
<b>Bleeder Hole Center To Threaded End Distance:</b>	0.219 Inches Minimum And 0.281 Inches Maximum
<b>Bleeder Hole Diameter:</b>	0.062 Inches Nominal
<b>Nominal Thread Size:</b>	0.750 Inches External
<b>Seat Angle:</b>	45.0 Degrees
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Style Designator:</b>	Plug, Machine W/bleeder Holes
<b>Thread Series Designator:</b>	Unf External

## How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.