

**Description**

outer diameter: 1/8", thread: 5/16-24, aluminum, AS5169 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[AN814-2D](#)

SKU / Model:	AS5169D02
Minimum Qty (MOQ):	5
NSN:	5365-00-585-6324
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6



\* See page 2 for technical characteristics

## P/N AS5169D02 Specifications

<b>Thread Class:</b>	3a External
<b>Thread Direction:</b>	Right-hand External
<b>Thread Length:</b>	0.249 Inches Nominal External
<b>Head Height:</b>	0.234 Inches Nominal
<b>Overall Length:</b>	0.546 Inches Nominal
<b>Connection Style:</b>	Plain
<b>Body Core Diameter:</b>	0.062 Inches Nominal
<b>Core Depth:</b>	0.265 Inches Nominal
<b>Bleeder Hole Center To Threaded End Distance:</b>	0.156 Inches Nominal
<b>Bleeder Hole Diameter:</b>	0.062 Inches Nominal
<b>Nominal Thread Size:</b>	0.312 Inches External
<b>Material:</b>	Aluminum Alloy 7075 Overall Or Aluminum Alloy 2014 Overall
<b>Material Document And Classification:</b>	Qq-a-268,t6 Fed Spec 1st Material Response Overall Or Qq-a-268,t851 Fed Spec 1st Material Response Overall Or Qq-a-266 Fed Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	Plug, Machine W/bleeder Holes
<b>Thread Series Designator:</b>	Unf External

## How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AS5169D02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.